



[www.nilcouk.com](http://www.nilcouk.com)

**James Briggs Ltd**  
Salmon Fields, Royton, Oldham, OL2 6HZ, UK  
Tel: 0161 627 0101  
WWW.nilcouk.com

## *TECHNICAL DATA SHEET* **FLOOR CLEANING GEL**

Cleaning System Code: H13

### 1. Introduction

A caustic alkali free, water based light duty cleaner designed primarily to clean and maintain impervious and coated floors.

### 2. Where to use

On all water resistant non-porous flooring, including polished and treated timbers, vinyl and composites, marble, terrazzo and all other conventional flooring materials. This product may also be used as a general purpose light duty cleaner for most other hard surfaces including painted walls, tiles etc. and will not affect floor sealants.

### 3. Where not to use

- No major restrictions other than on unsealed timbers where it may raise the grain.
- Where heavy duty cleaning performance is required.

### 4. Physical properties.

Appearance	A soft green/yellow gel with a pine odour.
pH	8.00 +/- 1.00
Specific Gravity	0.995 – 1.000
Non Volatiles % m/m	< 5.0
Active Content % m/m	4 - 8
Viscosity	14 – 16,000 cps [Brookfield DV-E Spindkle 7 @ 20rpm].
Flammability	This product is not flammable.
Composition Data	Water, non-ionic surfactants, synthetic thickener, synthetic fragrance, pH buffer, and a green/yellow dye.

### 5. Application Details

Prepare a solution of between 0.5 and 2.0% in warm or cold water. Stir to dissolve thoroughly. Apply with a mop, cloth or “squeegee” and allow to dry. Buff with a mop, cloth, or buffing machine if required.

### 6. Availability

Available in 5 Litre plastic jerricans.

*Product Reference SVTN5GLP, Dated May 2010*

*This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.*